



QWZU.EX15532 Centrifugal Fire Pumps, End Suction

[Page Bottom](#)

Centrifugal Fire Pumps, End Suction

[See General Information for Centrifugal Fire Pumps, End Suction](#)

NITIN VENTURES FZE

EX15532

PO BOX 262294

JEBEL ALI

JAFZA

DUBAI, UNITED ARAB EMIRATES

Rated Capacity GPM	Size In.	Model Dsg	Rated Net Pressure Range psi	Approx Speed RPM	Max Working Pressure psi
50	2 X 1 ¼	NVE32-20	44-84	2900	230
50	2 X 1 ¼	NVE32-20	78	2800	230
50	2 X 1 ¼	NVE32-26	68-107	2900	230
50	2 X 1 ¼	NVE32-26	64-100	2800	230
50	2 ½ X 2	NVE50-32H	109-203	2900	220
50	2 ½ X 2	NVE50-32H	102-189	2800	220
100	2 X 1 ¼	NVE32-26	65-104	2900	230
100	2 X 1 ¼	NVE32-26	60-96	2800	230
100	2 ½ X 2	NVE50-32H	109-203	2900	220
100	2 ½ X 2	NVE50-32H	101-189	2800	220
100	3 X 2 ½	NVE65-32H	107-209	2900	220
100	3 X 2 ½	NVE65-32H	100-195	2800	220
150	2 ½ X 2	NVE50-32H	107-203	2900	220
150	2 ½ X 2	NVE50-32H	99-189	2800	220
150	3 X 2 ½	NVE65-32H	106-207	2900	220
150	3 X 2 ½	NVE65-32H	98-193	2800	220
200	2 ½ X 2	NVE50-32H	104-203	2900	220
200	2 ½ X 2	NVE50-32H	97-190	2800	220
200	3 X 2 ½	NVE65-32H	104-205	2900	220
200	3 X 2 ½	NVE65-32H	97-191	2800	220
200	4 X 3	NVE80-32H	107-193	2900	220
200	4 X 3	NVE80-32H	99-180	2800	220
250	2 ½ X 2	NVE50-32H	98-204	2900	220
250	2 ½ X 2	NVE50-32H	90-190	2800	220
250	3 X 2 ½	NVE65-32H	103-204	2900	220
250	3 X 2 ½	NVE65-32H	96-191	2800	220

250	4 X 3	NVE80-32H	107-193	2900	220
250	4 X 3	NVE80-32H	99-180	2800	220
250	5 X 4	NVE100-32H	107-201	2900	220
250	5 X 4	NVE100-32H	100-187	2800	220
300	3 X 2 ½	NVE65-32H	101-207	2900	220
300	3 X 2 ½	NVE65-32H	94	2800	220
300	4 X 3	NVE80-32H	106-193	2900	220
300	4 X 3	NVE80-32H	99-180	2800	220
300	5 X 4	NVE100-32H	107-201	2900	220
300	5 X 4	NVE100-32H	100-187	2800	220
400	4 X 3	NVE80-32H	104-194	2900	220
400	4 X 3	NVE80-32H	97-181	2800	220
400	5 X 4	NVE100-32H	107-201	2900	220
400	5 X 4	NVE100-32H	99-188	2800	220
450	4 X 3	NVE80-32H	103-194	2900	220
450	4 X 3	NVE80-32H	96-181	2800	220
450	5 X 4	NVE100-32H	106-202	2900	220
450	5 X 4	NVE100-32H	98-188	2800	220
500	4 X 3	NVE80-32H	102-194	2900	220
500	4 X 3	NVE80-32H	94-180	2800	220
500	5 X 4	NVE100-32H	104-202	2900	220
500	5 X 4	NVE100-32H	97-188	2800	220
750	5 X 4	NVE100-32H	100-203	2900	220
750	5 X 4	NVE100-32H	92-188	2800	220

Last Updated on 2015-07-13

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".



QXJY.EX15561 Centrifugal Fire Pumps, Split Case

[Page Bottom](#)

Centrifugal Fire Pumps, Split Case

[See General Information for Centrifugal Fire Pumps, Split Case](#)

NITIN VENTURES FZE

EX15561

PO BOX 262294

JEBEL ALI

JAFZA

DUBAI, UNITED ARAB EMIRATES

Fire pumps, single stage

Rated Capacity (gpm)	Size (in.)	Model Dsg	Rated Net Pressure Range (psi)	Approx Speed (rpm)	Max Working Pressure (psi)
50	4x3	NVS 80-30	92 - 54	2900	250
50	4x3	NVS 80-30	85 - 143	2800	250
100	4x3	NVS 80-30	92 - 154	2900	250
100	4x3	NVS 80-30	86 - 143	2800	250
100	5x4	NVS 100-30	96 - 173	2900	250
100	5x4	NVS 100-30	90 - 161	2800	250
150	4x3	NVS 80-30	91 - 154	2900	250
150	4x3	NVS 80-30	85 - 143	2800	250
200	4x3	NVS 80-30	91 - 153	2900	250
200	4x3	NVS 80-30	85 - 143	2800	250
250	4x3	NVS 80-30	91 - 152	2900	250
250	4x3	NVS 80-30	85 - 142	2800	250
250	5x4	NVS 100-30	96 - 172	2900	250
250	5x4	NVS 100-30	90 - 160	2800	250
300	4x3	NVS 80-30	91 - 151	2900	250
300	4x3	NVS 80-30	84 - 141	2800	250
300	5x4	NVS 100-30	96 - 171	2900	250
300	5x4	NVS 100-30	89 - 160	2800	250
400	4x3	NF80-380H	200 - 261	2900	290
400	4x3	NVS 80-30	87 - 151	2900	250
400	4x3	NVS 80-30	80 - 141	2800	250
400	5x4	NVS 100-30	93 - 171	2900	250
400	5x4	NVS 100-30	86 - 159	2800	250
450	5x4	NVS 100-30	92 - 170	2900	250
450	5x4	NVS 100-30	85 - 158	2800	250

500	5x4	NVS 100-30	90 - 168	2900	250
500	5x4	NF100-380H	198 - 225	2900	290
500	5x4	NVS 100-30	84 - 156	2800	250
750	6x5	NVS 125-30	109 - 177	2900	250
750	5x4	NF100-380H	193 - 223	2900	290
750	6x5	NVS 125-30	100 - 165	2800	250
750	6x5	NVS 125-30	84 - 142	2600	250
750	6x5	NVS 125-30	70 - 121	2400	250
1000	6x5	NVS 125-30	98 - 176	2900	250
1000	6x5	NF125-380H	192 - 226	2900	290
1000	8x5	NF125-480	82 - 110	1450	290
1000	6x5	NVS 125-30	91 - 164	2800	250
1000	6x5	NVS 125-30	77 - 141	2600	250
1000	6x5	NVS 125-30	64 - 119	2400	250
1250	6x5	NVS 125-30	172	2900	250
1250	8x6	NF150-560	121 - 146	1450	290
1250	6x5	NVS 125-30	160	2800	250
1500	8x6	NF150-560	119 - 144	1450	290
2000	10x8	NF200-480	86 - 110	1450	290
2500	12x8	NF200-540	113 - 134	1450	290
3500	14x10	NF250-500	100 - 102	1450	230

Last Updated on 2015-06-29

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".