



GFGV.EX15965 Foam Liquid Concentrates

[Page Bottom](#)

Foam Liquid Concentrates

[See General Information for Foam Liquid Concentrates](#)

NITIN VENTURES FZE

EX15965

PO BOX 262294

JEBEL ALI

JAFZA

DUBAI, UNITED ARAB EMIRATES

NITIE AFFF 3%, nominal 3 percent Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

NITIE AFFF 3%, nominal 6 percent Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

NITIE FFFP 6%, nominal 6 percent Film Forming Fluoroprotein Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

Foam concentrates for use with the following equipment.

NITIE AFFF 3%, 3 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 3, inlet pressure of 105 psi with 15m (44 ft) of 2-1/2 in. hose between inductor and Angus Fire (UK), Model F225HU nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	65

NITIE AFFF 6%, 6 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 6, inlet pressure of 120 psi with 15m (44 ft) of 2-1/2 in. hose between inductor and Angus Fire (UK), Model F225HU nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	70

NITIE FFFP 6%, 6 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 6, inlet pressure of 120 psi with 15m (44 ft) of 2-1/2 in. hose between inductor and Angus Fire (UK), Model F225HU nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	70

[Last Updated](#) on 2011-10-13

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)



GFGV.EX16131 Foam Liquid Concentrates

[Page Bottom](#)

Foam Liquid Concentrates

[See General Information for Foam Liquid Concentrates](#)

EUROTECH FIRE PROTECTION LTD

EX16131

The Business Centre
Unit 6
Molly Millars Lane
Wokingham, RG41 2QZ UNITED KINGDOM

Eurotech AFFF 6%, nominal 6 percent, Aqueous Film Forming Foam, 35 F minimum storage and use temperature. Hydrocarbon fuels only.

Eurotech AFFF 3%, nominal 3 percent, Aqueous Film Forming Foam, 35 F minimum storage and use temperature. Hydrocarbon fuels only.

Eurotech FP3%, nominal 3 percent Flouroprotein, 35 F minimum storage and use temperature. Hydrocarbon fuels only.

Eurotech FP6%, nominal 3 percent Flouroprotein, 35 F minimum storage and use temperature. Hydrocarbon fuels only

Eurotech Plus AR AFFF 3/3 3%, +35 F minimum storage and use temperature. Hydrocarbon fuels at 3 percent. Polar solvent fuels at 3 percent.

Eurotech AR AFFF 3/3 3%, +35 F minimum storage and use temperature. Hydrocarbon fuels at 3 percent. Polar solvent fuels at 3 percent.

Eurotech Plus AR AFFF 3/6 6%, +35 F minimum storage and use temperature. Hydrocarbon fuels at 3 percent. Polar solvent fuels at 6 percent.

Eurotech AR AFFF 3/6 6%, +35 F minimum storage and use temperature. Hydrocarbon fuels at 3 percent. Polar solvent fuels at 6 percent.

Eurotech FFFP 3%,+20 F minimum storage temperature. Hydrocarbon fuels at 3 percent.

Foam concentrates for use with the following equipment.

Eurotech AFFF 6%, 6 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire Armour, Model UNI225, 2-1/2 in. size, set at 6, inlet pressure of 142 psi with 100 ft of 1-1/2 in. hose between inductor and Angus Fire Armour, Model F225HU nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire Armour, Model F225HU	2-1/2	85

PROPORTIONERS - FIXED IN-LINE INDUCTORS

Description	Size In.	Orifice Diam In.	Inlet Pressure psi	Back Pressure psi
Angus, Model IND-40	1-1/2	0.16(4 mm)	131	81

PROPORTIONERS-BLADDER TANK WITH CONTROLLER

Description	Controller Size In.	Orifice Size In.	Flow GPM
Arrow Tank Engineering	3	0.502	310-920

SPRINKLERS

Fuel	Style	Min Application Rate GPM/Sq Ft	Min Inlet Pressure psi
Tyco Fire , Model B1			
Hydrocarbons	Pendant	0.16	30

Eurotech AFFF 3%, 3 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire Armour, Model UNI225, 2-1/2 in. size, set at 3, inlet pressure of 92.5 psi with 148 ft of 1-1/2 in. hose between inductor and Angus Fire Armour, Model F225U nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire Armour, Model F225U	2-1/2	50

PROPORTIONERS - FIXED IN-LINE INDUCTORS

Description	Size In.	Orifice Diam In.	Inlet Pressure psi	Back Pressure psi
Angus, Model IND-40	1-1/2	0.16(4 mm)	142	81

PROPORTIONERS-BLADDER TANK WITH CONTROLLER

Description	Controller Size In.	Orifice Size In.	Flow GPM
Arrow Tank Engineering	3	0.354	300-900

SPRINKLERS

Fuel	Style	Min Application Rate GPM/Sq Ft	Min Inlet Pressure psi
Tyco Fire, Model B1			
Hydrocarbons	Pendant	0.16	30

FOAM MONITORS

Monitor	Nozzle	Type	Nozzle Inlet Pressure, psi
Shah Bhogilal, AAAG FM 500	500 GPM	Self-Inducting	100
Shah Bhogilal, AAAG FM 750	750 GPM	Self-Inducting	100
Shah Bhogilal, AAAG FM 1000	1000 GPM	Self-Inducting	100
Shah Bhogilal, AAAG FM 500	750 GPM	for use with Model AAAG 750 JRC	100
Shah Bhogilal, AAAG FM 500	1000 GPM	for use with Model AAAG 1000 JRC	100
AAAG FMV 500- 750	500-750 GPM at 500	Self Inducting	100
AAAG FMV 500- 750	500-750 GPM at 750	Self Inducting	100
AAAG FMV 500-750-1000	500-750-1000 GPM at 500	Self Inducting	100
AAAG FMV 500-750-1000	500-750-1000 GPM at 750	Self Inducting	100
AAAG FMV 500-750-1000	500-750-1000 GPM at 1000	Self Inducting	100
AAAG FMV 500-750-1000	500-750-1000 GPM at 500	For use with Model AAAG JRC 500	100
AAAG FMV 500-750-1000	500-750-1000 GPM at 750	For use with Model AAAG JRC 750	100
AAAG FMV 500-750-1000	500-750-1000 GPM at 1000	For use with Model AAAG JRC 1000	100

EUROTECH FP3%, 3 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 3, inlet pressure of 100 psi with 45m of 1-1/2 in. hose between inductor and Angus Fire (UK), Model F225U nozzle

PROPORTIONERS - FIXED IN-LINE INDUCTORS

Description	Size In.	Orifice Diam In.	Inlet Pressure psi	Back Pressure psi
Angus, Model IND-40	1-1/2	0.16(4mm)	142	82

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	60

SPRINKLERS

Fuel	Style	Min Application Rate GPM/Sq Ft	Min Inlet Pressure psi
Tyco Fire, Model B1			
Hydrocarbons	Pendant	0.16	30

EUROTECH FP6%, 6 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 6, inlet pressure of 100 psi with 15m of 1-1/2 in. hose between inductor and Angus Fire (UK), Model F225U nozzle.

PROPORTIONERS - FIXED IN-LINE INDUCTORS

Description	Size In.	Orifice Diam In.	Inlet Pressure psi	Back Pressure psi
Angus, Model IND-40	1-1/2	0.16(4 mm)	131	82

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	60

SPRINKLERS

Fuel	Style	Min Application Rate GPM/Sq Ft	Min Inlet Pressure psi
Tyco Fire, Model B1			
Hydrocarbons	Pendant	0.16	30

EUROTECH PLUS AR AFF 3/3 3%, 3 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 3AR, inlet pressure of 93 psi with 30m of 1-1/2 in. hose between inductor and Angus Fire (UK), Model F225U nozzle

PROPORTIONERS - FIXED IN-LINE INDUCTORS

Description	Size In.	Orifice Diam In.	Inlet Pressure psi	Back Pressure psi
Angus, Model IND-40	1-1/2	0.19(4.7mm)	160	87

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	55

FIXED FOAM DISCHARGE OUTLETS

Description	Orifice Diam In.	Inlet Pressure psi
Angus, Model TPS-50MKV	0.59(15mm)	87

Where:

Fuel	Min Application Rate, GPM/ft ²
------	--